

632XR RAPISCAN

A GENEROUS TUNNEL SIZE AND HEAVY DUTY ROLLER BED CAN SCREEN SECURED PALLETS AND CARGO WITHOUT UNWRAPPING

- **E** LOW POWER CONSUMPTION
- PHEAVY DUTY ROLLER BED
- 150KV OR 200KV GENERATOR
- EXPLOSIVES AND NARCOTICS DETECTION ALERT

STANDARD FEATURES

- Multi energy imaging (4 Color)
- View previous/next bag
- Image archive
- · Configurable image processing keys
- Baggage counter
- Date / time display
- Search indicator
- UPS (Uninterrupted Power Supply)
- Multi language support
- · Flat panel monitor

STANDARD IMAGE PROCESSING FUNCTIONS

- Crystal clear[™]
- Black and white
- Organic / inorganic stripping
- Inverse video
- High penetration
- Pseudo color
- Low penetration
- · Variable edge enhancement
- Variable color stripping
- Variable gamma
- Variable density
- Dynamic continuous zoom & panning
- Fixed zoom (64x)



TUNEL OPENING (WXH): 1,537 x 1,650 mm (60.5 x 65.0 in)

WITH A LARGE TUNNEL OPENING, A HEAVY-DUTY ROLLER BED, AND TWO X-RAY GENERATOR OPTIONS, THE RAPISCAN 632XR IS DESIGNED TO INSPECT PALLETS AND OTHER LARGE CARGO WEIGHING UP TO 3,000 KGS (6,614 POUNDS) WITHOUT COMPROMISING THROUGHPUT.

DETECTION OF EXPLOSIVES AND NARCOTICS ALERT

Target™ and NARCScan™ are designed to assist operators in the detection of a range of explosives and narcotics respectively in real time during the scanning process by marking a potential threat on the X-ray image. Rapiscan detection algorithms are based on regulatory material analysis techniques.

EASE OF USE PROVIDING HIGHEST THROUGHPUT

With over 13 image processing tools and detection alert algorithms the feature rich software allows the operator to more easily and accurately search for contraband.

MEETING TODAY'S MOST STRINGENT GLOBAL REQUIREMENTS

Rapiscan 632XR meets the most rigorous detection and image quality requirements as set by the U.S. Transportation Security Administration (TSA), and French civil aviation authority (STAC).

REGULATORY COMPLIANCE

Rapiscan 632XR performance is in full compliance with the European Union regulations (EC) No. 300/2008, (EU) No. 2015/1998 and Commissions Decision C (2015) 8005 for aviation security.









632XR **RAPISCAN**

Tunnel size:

Conveyor speed:

Conveyor load (Max):

632XR outline with 150kV X-ray Generator

PHYSICAL SPECIFICATIONS

Dimensions: Length: 6,430mm

> Width: 2,873 mm Height: 2,181 mm 1,537mm x 1,650 mm 0.20 m/sec (39.4 ft./min)

3,000 Kg (6,614 lbs) at 230V 1,500 Kg (3,307 lbs) at 115V

Conveyor height (Approx.): 304 mm (12.0 in.) Weight (Approx.): Net: 2,782 Kg (6,133 lbs) System power: 115/230 VAC +- 10% / 60/50Hz

X-RAY GENERATOR AND IMAGE PERFORMANCE¹

30 mm typical; 28 mm standard Steel penetration: Resolution: 40 AWG typical; 38 AWG standard Cooling: Sealed oil bath with forced air

Anode voltage: Operating at 150kV

Tube current: 1.5 mA Orientation: Horizontal

OPERATING ENVIRONMENT

Storage temperature: -20°C to 50°C Operating temperature: 0°C to 40°C

Relative humidity: 5 to 95% non-condensing

PROTECTION CLASS

System: IP20 IP43² Operator control panel:

GOVERNMENT REGULATORY

TSA Air Cargo Screening Technology List (ACSTL) Qualified

Transport Canada (TC) Air Cargo Qualified Regulation (EC) No. 300/2008 Compliant Regulation (EU) No. 2015/1998 Compliant

EU Commissions Decision (EU) C(2015) 8005 Compliant

French Civil Aviation Authority (STAC) Certified

HEALTH & SAFETY

Rapiscan Systems' cabinet X-ray products comply with all applicable U.S. FDA and equivalent international regulatory agency requirements, contained in the cabinet X-ray radiation safety performance standard [21 CFR 1020.40] and the general performance standard [21 CFR Part 1010] as well as IEC standard 61010-2-091. Rapiscan baggage and parcel inspection systems radiation emission leakages are well below the required regulatory limits with less than 1 µSv/hr at 10 cm from all surfaces of cabinet X-ray

OPTIONS AND ACCESSORIES

- Explosives detection alert (Target™)
- Narcotics detection alert (NARCScan™)
- Density threshold alert (DTA)
- Threat image projection (TIP)
- Threat image projection network (TIPNet)
- Remote image archive review (NETView™)
- Retwork x-ray management automation and link system (NEXLink ™)
- Multi-system network display station (NDS)
- Automatic image archiving
- Enhanced image archiving
- Operator training program (OTP)
- Manual scan
- Foot mat
- Smartcard login
- Power conditioner
- Conveyor accessories
- Universal Printer Support

(1) Stated performance as measured by Rapiscan Imaging Validation Test Kit. (2) With optional replaceable cover.

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice. Product pictures are for general reference. Please note that due to US laws and regulations, not all Rapiscan products are available for sale in all countries without restriction. Please contact your Rapiscan Systems sales representative for more information.

HTDS

Parc d'Activités du Moulin de Massy - 3 rue du Saule Trapu

BP246 - 91882 Massy Cedex France

Tel: +33 (0) 1 64 86 28 28 - Fax: +33 (0) 1 69 07 69 54 - info@htds.fr - www.htds.fr

HTDS Algeria: +213 232 384 01/02 HTDS Morocco: +212 222 749 59 HTDS Egypt: +202 229 053 06 HTDS Madagascar: +261 34 40 664 72

HTDS Lybia: +218 91 69 50 70 8 HTDS Tunisia: +216 70 836 961